

**A**  **S**

**HARDWARE  
&  
ACCESSORY**

**GRINDING DISC**



**ACS Grinding Disc** is made of Aluminium oxide with metal ring. It performing faster grinding and gives a longer life in abrasives machining.

- ✓ High quality & performance
- ✓ Remarkable features are big aggressiveness
- ✓ Rigid construction and longer life span
- ✓ Best material removal capacity



**Available size**

Product	Part No.	Size (mm)	Max Speed (RPM)	Pcs/box	Pcs/Ctn
ACS Grinding Disc - 4"	01-GDIS-100616	100 x 6 x 16	13700	25	200
ACS Grinding Disc - 5"	01-GDIS-125622	125 x 6 x 22	10700	25	100

**CUTTING DISC**



**ACS Cutting Disc** is made of Aluminium oxide with metal ring. It performing faster cutting and gives a longer life in abrasives machining.

- ✓ High quality & performance
- ✓ Remarkable features are big aggressiveness
- ✓ Rigid construction and longer life span
- ✓ Best material removal capacity



**Available size**

Product	Part No.	Size (mm)	Max Speed (RPM)	Pcs/Box	Pcs/Ctn
ACS Cutting Disc - 4"	01-CDIS-1052216	105 x 2.2 x 16	13700	50	400
ACS Cutting Disc - 5"	01-CDIS-125322	125 x 3 x 22	10700	50	200
ACS Cutting Disc - 14"	01-CDIS-3553254	355 x 3 x 25.4	4400	50	14

**RECIPROCATING SAW BLADE**



**ACS Reciprocating Saw Blade** provides industry-leading cutting performance for professional tradesman. It delivers precision-ground teeth and thick blades for high performance in wood and metal cutting.

- ✓ Flexible flush cut, fast cut
- ✓ Flexible blade for metal with the advantage of a HCS back and HSS cutting edge
- ✓ Fast and easy heavy metal cutting
- ✓ Optimized for higher performance

**Available size**

Product	Part No.	Size	Packing
ACS Reciprocating Saw Blade	06-BLDE-22514TPI	225 mm (9") x 19 mm x 0.9 mm	5 Pieces / Pack 10 Packs / Box



**WELDING ELECTRODE**



**ACS Welding Electrode** provides guaranteed performance and delivers superior quality for general purpose welding electrodes, TIG & MIG wires, stainless steel electrodes, fluxes, and electrode and flux ovens to meet your welding needs at lower cost.

- ✓ Low mild steel type electrodes with titanium coating
- ✓ Suitable for both AC and DC, can weld in all position
- ✓ Manipulate is free
- ✓ Restrike is easy

**Available size**

Product	Part No.	Size (mm)	Max Speed (RPM)
ACS E6013 Welding Electrode	25-WELE-26300	2.6 x 300	20 kg/ctn
ACS E6013 Welding Electrode	25-WELE-32350	3.2 x 350	20 kg/ctn
ACS E6013 Welding Electrode	25-WELE-40400	4.0 x 400	20 kg/ctn



**ALUMINIUM TAPE**



**ACS Aluminium Tape** is a self-adhesive & 40-micron thick aluminium foil is coated one side with a Solvent sensitive adhesive. The tape is backed with a strong polyethylene laminated paper coated with silicone.

- ✓ Flame retardant and self-extinguishing
- ✓ High water and temperature resistant
- ✓ Easy unwind and tear
- ✓ Excellent reflection of both heat and light.
- ✓ Very low moisture vapor transmission rate

**Available size**

Product	Part No.	Thickness	Dimension	Packing
ACS Aluminium Tape	19-ALUT-05040	40Micron	63mm X 40 m	20 Rolls / Ctn



**MASKING TAPE**



**ACS Masking Tape** is a type of pressure sensitive tape made of a thin and easy-to-tear paper, and an easily released pressure sensitive adhesive.

- ✓ Excellent adhesion high tensile strength
- ✓ Leave no residue after peeling off
- ✓ Good resistant of damage
- ✓ Hand tear-able
- ✓ Controlled unwind for ease of use and reduced waste

**Available size**

Product	Part No.	Dimension	Packing
ACS Masking Tape	19-MAST-03640	36mm X 40 m	96 Rolls / Ctn



**COTTON TWINE**



**ACS Cotton Twine** is 100% made from natural cotton, soft and pliable, and easy on the hands. It is stronger for those tough projects and used for seine twine, chalk, and mason line.

- ✓ 100% natural cotton
- ✓ Strong and high durability
- ✓ High tensile
- ✓ Medium weight
- ✓ Handles easily
- ✓ Pollution free
- ✓ Soft, extremely flexible

**Available Size**

Product	Part No.	Dimension	Packing
ACS Cotton Twine	16-CTWE-072514	0.72mm x 514m	10 pcs/box; 10 box/ctn



**RECYCLE GARBAGE BAG**



**ACS Recycle Garbage Bag/ Trash Bag** is super resistant quality used for industrial purposes.

**Available Size**

Product	Part No.	Size	Packing
ACS Recycle Garbage	19-GBAG-36 X 48-Black	36" x 48"	40 pcs / pkt; 10 pkt / woven resin bag



**LDPE BAG (PU BAG)**



**ACS LDPE Clear Plastic Bag** is a cost effective, premium grade, 100% virgin material.

**Available Size**

Product	Part No.	Dimension	Packing
ACS LDPE	19-PBAG-09X14	0.04mm x 09 x 14	5LBS/Pack (10Pack / Carton)





**THERMOMETER**



**ACS Thermometer** is a V-shape; gold-colored plated which made of nylon material. This particular material has excellent strength, impact and stiffness properties which makes it perfect for the toughest applications. Some of the uses are process piping, tanks, and pipelines in building construction, boilers and air ducts.

- ✓ Ruggedness and durability
- ✓ Aluminum body
- ✓ Brass connection
- ✓ Straight / Angle 90° backward

**Available size**

Product	Part No.	Range
ACS Thermometer (Straight)	21-THER-ST063150	-30~50°C
	21-THER-ST100150	-30~50°C
ACS Thermometer (90° Angled)	21-THER-AL063150	-30~50°C
	21-THER-AL100150	-30~50°C



**PRESSURE GAUGE**



**ACS Pressure Gauge** ideally suited to most industrial applications where accuracy and durability is required. Air, oil, gas, or water services are the most common applications. The pressure gauge is available in 0~150 psi, 0~200 psi, 0~300 psi, and 0~500 psi with 100 mm dial diameter.

- ✓ ISO 9001-2008 certified
- ✓ ±1.5% of accuracy
- ✓ PSI as primary unit
- ✓ kgf/cm2 as secondary unit

**Available size**

Product	Part No.	Range (PSI)
ACS Pressure Gauge	21-PEGE-4150	0~150
	21-PEGE-4200	0~200
	21-PEGE-4300	0~300
	21-PEGE-4500	0~500



**PTFE SEAL TAPE**



**ACS PTFE Seal Tape** is a cost effective, premium grade, more flexible and improved diffusion seal capability and easier to work with. Thread tape is appropriate for use on tapered threads, where the sealing force is a wedge action.

- ✓ Resist corrosion
- ✓ Resist aging
- ✓ Resist high temperature
- ✓ Superior sealing

**Available size**

Product	Part No.	Dimension	Packing
ACS PTFE Seal Tape	21-PTFE-0120110	12mm X 0.1mm X 10m	1000 Rolls (10Boxes / Carton)



**PTFE SEAL TAPE**



**ACS Quality Cotton Gloves** offer protection and comforting care for the sensitive skin on your hands. Also it forms a protective barrier between the environment and sensitive skin,

Type: Safety Gloves

Material: Cotton

Color: Natural white

Features: Seamless Knitted, high-quality, cheap price, super warm, antistatic, anti-pilling, durable

**Available size**

Product	Part No.	Packing
ACS Quality Cotton Gloves	24-CGLV-700	12Pairs/Dozen (700 gms) 50 Dozen/Gunny Sack



**SS FLEXIBLE HOSE**



**ACS SUS304 Flexible Hose** having a high percentage of braid protects the corrugated hose from damaging by ambient environment.

- √ Portion in contact with fluid is stainless steel.
- √ High corrosion resistance and high durability

Product	Part No.	Diameter	Length
ACS S210 Flexible Hose with GI Union End	21-SSFH-020300	3/4 "	200/250mm
	21-SSFH-025300	1 "	250/300mm
	21-SSFH-032300	1-1/4 "	250/300mm
	21-SSFH-040300	1-1/2 "	250/300mm
	21-SSFH-050300	2"	250/300mm
	21-SSFH-065300	2-1/2 "	250/300mm
ACS F110 Flexible Hose with GI PN16 Flanged End	21-SSFH-065200	2-1/2 "	200mm
	21-SSFH-080200	3"	200mm
	21-SSFH-100200	4"	200mm
	21-SSFH-125200	5"	200mm
	21-SSFH-150200	6"	200mm



**Application Fluid:** Water & Air

**RUBBER FLEXIBLE JOINT**



**ACS DOUBLE SPHERE THREADED UNION STYLE 30**

- √ Superb absorption vibration
- √ Effective for large eccentricity thermal and bending angle
- √ BSPT, threaded unions

Diam. De mm (in.)	L (mm)	Allowable Movement (mm)			
		Axial Compression	Axial Elongation	Transverse Deflection	Angular Deflection
20	200	22	6	22	45°
25	200	22	6	22	45°
32	200	22	6	22	45°
40	200	22	6	22	45°
50	200	22	6	22	45°
65	240	22	6	22	45°



**ACS SINGLE SPHERE EXPANSION JOINT STYLE 10**

- √ Allow for four way movements
- √ Excellent ability to absorb vibration and sound
- √ Corrosion resistant

Diam. D mm (in.)	L (mm)	Allowable Movement			
		Axial Compression	Axial Elongation	Transverse Deflection	Angular Deflection
65	200	1/2"	3/8"	±1/2"	15°
80	200	1/2"	3/8"	±1/2"	15°
100	200	5/8"	3/8"	±1/2"	15°
125	200	5/8"	3/8"	±1/2"	15°
150	200	5/8"	3/8"	±1/2"	15°
200	200	5/8"	3/8"	±1/2"	15°
250	200	3/4"	1/2"	±3/4"	15°
300	200	3/4"	1/2"	±3/4"	15°



**OPERATING CONDITION**

**Application Fluid:** Water & Air

**Pressure Bar:** 16; 225 psi

**Temperature °C:** -10 to 80 Deg C



## Accise Asia Pacific Pte Ltd

Block 3017A, Ubi Road 1, #01-12,  
Singapore 408709

**Tel:** +65 6748 4292 | **Fax:** +65 6749 0844

**Email:** sales@accise-asia.com

**Web:** www.accise-asia.com

### AUTHORISED DISTRIBUTOR:

